

550R SERIES

3/4" GEAR-DRIVEN ROTOR



550R Rotor

**FAST AND
EASY,
BUT WELL
ADJUSTED.**

KEY FEATURES & BENEFITS

FAMILIAR TOP ADJUSTMENT, WET OR DRY
For fast convenient installation

REVERSING FULL- AND PART-CIRCLE OPERATION
Allows you to adjust the rotor from 40° to 360°

NON-FLUSHING WIPER SEAL
Reduces leaks caused by debris trapped under the seal

3/4" INLET
Replaces all standard rotors

ALL ADJUSTMENTS MADE WITH A STANDARD SCREWDRIVER
No special tools required

STANDARD RUBBER COVER
Provides added protection against debris and keeps playing areas safe

WIDE SELECTION OF NOZZLES
8 Standard and 4 Low Angle nozzles included with each rotor to handle a wide range of applications

POSITIVE LEFT AND RIGHT STOPS (FIXED LEFT STOP)
Reduces set-up time by allowing you to quick check the arc

OPTIONAL CHECK VALVE HOLDS UP TO 7' OF ELEVATION CHANGE
Eliminates water waste

The new Irritrol® 550R rotor delivers basic simplicity and dependable action all in one rotor. With its proven 3/4" gear-driven design, 50' of watering radius and a full 5" pop-up, this rotor just gets more done. Installation is made simple with Irritrol's familiar top arc adjustment and all-in-one full- and part-circle operation from 40 to 360 degrees. And, with the ability to quick check the arc with positive left and right stops, set-up time is further reduced. The 550R comes with a wide selection of nozzles (8 standard and 4 low angle nozzles) making it the ideal rotor for your everyday installations. Irritrol. **Get more done.**


OPERATING SPECIFICATIONS

- Inlet: ¾" female-threaded NPT
- Adjustable arc range: 40° to 360°
- Flow range: .74 – 9.70 gpm
- Recommended operating pressure: 45 psi
- Precipitation rate: .20 – 1.01 inches per hour
- Overall height (retracted): 7 3/8"
- Radius: 25' – 50'
- Pressure range: 25 to 65 psi
- Standard nozzle trajectory: 25°
- Low angle nozzle trajectory: 12°
- 8 standard and 4 low angle nozzles included
- Riser height: 5"
- Five-year warranty

OPTIONAL ACCESSORIES

- Recycled-water indicator cover (purple)
- Field-installable check valve

SPECIFYING INFORMATION



550R ROTOR

PERFORMANCE DATA

550R Rotor - Standard Nozzle

Nozzle	Pressure psi	Radius ft.	Flow GPM	Precip. ■ in/h	Precip. ▲ in/h
1.5	25	33	1.15	0.20	0.23
	35	34	1.38	0.23	0.27
	45	35	1.59	0.25	0.29
	55	35	1.74	0.27	0.32
	65	36	1.88	0.28	0.32
2.0	25	35	1.45	0.23	0.26
	35	36	1.80	0.27	0.31
	45	37	2.12	0.30	0.34
	55	37	2.30	0.32	0.37
	65	37	2.58	0.36	0.42
2.5	25	35	1.75	0.28	0.32
	35	36	2.20	0.33	0.38
	45	37	2.55	0.36	0.41
	55	37	2.80	0.39	0.45
	65	37	3.05	0.43	0.50
3.0	25	36	2.20	0.33	0.38
	35	38	2.60	0.35	0.40
	45	40	3.05	0.37	0.42
	55	40	3.52	0.42	0.49
	65	40	3.80	0.46	0.53
4.0	25	37	2.95	0.41	0.48
	35	40	3.55	0.43	0.49
	45	42	4.10	0.45	0.52
	55	42	4.45	0.49	0.56
	65	43	4.85	0.50	0.58
5.0	25	39	3.75	0.47	0.55
	35	41	4.50	0.52	0.60
	45	43	5.10	0.53	0.61
	55	45	5.75	0.55	0.63
	65	45	6.10	0.58	0.67
6.0	25	39	4.20	0.53	0.61
	35	43	5.20	0.45	0.63
	45	44	6.05	0.60	0.69
	55	47	6.65	0.58	0.67
	65	48	7.25	0.61	0.70
8.0	25	36	5.75	0.85	0.99
	35	43	7.10	0.74	0.85
	45	46	8.05	0.62	0.72
	55	48	8.95	0.69	0.80
	65	50	9.70	0.75	0.86

550R Rotor - Low Angle Nozzle

Nozzle	Pressure psi	Radius ft.	Flow GPM	Precip. ■ in/h	Precip. ▲ in/h
1.0 LA	25	25	0.74	0.23	0.26
	35	28	0.94	0.23	0.27
	45	29	1.03	0.23	0.27
	55	29	1.14	0.26	0.30
	65	29	1.25	0.29	0.33
1.5 LA	25	27	1.10	0.29	0.34
	35	30	1.35	0.29	0.33
	45	31	1.52	0.30	0.35
	55	31	1.75	0.35	0.40
	65	31	1.90	0.38	0.44
2.0 LA	25	29	1.40	0.32	0.37
	35	31	1.72	0.34	0.40
	45	32	2.05	0.39	0.45
	55	33	2.25	0.40	0.46
	65	33	2.45	0.43	0.50
3.0 LA	25	29	2.20	0.50	0.58
	35	33	2.60	0.46	0.53
	45	35	3.05	0.48	0.55
	55	36	3.40	0.51	0.58
	65	36	3.70	0.55	0.63

1. Precipitation rates based on half-circle operation
2. ■ square spacing based on 50% diameter of throw
3. ▲ triangular spacing based on 50% diameter of throw

Note: Data collected in zero wind conditions